



## DESCRIPTION

Type	Track Spotlight
Article-number	141279L11777
Colour	white
Energy Consumption	19.1 W
Efficiency	123 lm/W
Luminous Flux	2344 lm
Current (sec)	500 mA
Protection Class	IP 20
Energy-Label	D
Cooling	Passive

## LED

Color Temperature	3000K
Color Rendering	CRI 92
LES	15
Color Tolerance	3-Step McAdam
Planckian Curve	BBBL
Spectrum	Premium White G7
Photobiological safety	RG2

## ELECTRICAL


Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	3-Phase Adapter
Max Luminaires MCB	B16A 27 pcs
Tracks	Global Stucchi Eutrac

## Control

Control	CASAMBI
Dimming Range	1-100 %

## REFLECTOR

Technology	ULTRA
Material	Miro 20 Silver
FWHM	64°
FWTM	84°



I-max : 2353 cd \*

UGR : 23.1 (4H/8H - 70/50/20)

H/m	D/m	E <sub>max</sub> /lx/klm *
1.0	1.2	963
2.0	2.5	241
3.0	3.7	107
4.0	5.0	60

## Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023\_05\_22