



CASAMBI DALI RoHS CE

GENERAL

Article-number	141292
Type	Track Spotlight
colours	silver, black, white
Power consumption	< 33 W
Efficiency	83 lm/W .. 154 lm/W
Luminous Flux	1731 lm .. 4283 lm
Energy-Label	F .. C
Protection Class	IP
Cooling	Passive

LED

CRI	CRI > 82 -> 92
Color Temperature	2700K, 3000K, 3500K, 4000K
Color Tolerance	3-Step McAdam


ELECTRICAL

Wiring / Adapter	3-Phase Adapter
Safety Class	1
Startup Time	< 1 s
Overload Protection	
Short Circuit Protection	
Power Supply	220-240 50-60Hz
Environment	0° - 30°C typical Ta 25°C

Control

Control	DALI, ON/OFF, CASAMBI
Dimming Range	1-100 %

REFLECTORS : ULTRA Technology



Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023_05_09