



DESCRIPTION

Type	Swivel
Article-number	141296L10297
Colour	white
Energy Consumption	26.7 W
Efficiency	109 lm/W
Luminous Flux	2904 lm
Current (sec)	700 mA
Protection Class	IP
Energy-Label	E
Cooling	Passive

LED

Color Temperature	3000K
Color Rendering	CRI 92
LES	15
Color Tolerance	3-Step McAdam
Planckian Curve	BBBL
Spectrum	Premium White G7
Photobiological safety	RG2

ELECTRICAL


Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	connector 3/5 Pol (DALI)
Max Luminaires MCB	B16A - 50 pcs

Control

Control	CASAMBI
Dimming Range	100 %

REFLECTOR

Technology	ULTRA
Material	Miro 8 Silver
FWHM	20°
FWTM	40°



I-max : 14592 cd *

UGR : 21.1 (4H/8H - 70/50/20)

H/m	D/m	E _{max} /lx/klm *
1.0	0.3	5025
2.0	0.7	1256
3.0	1.0	558
4.0	1.4	314

Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023_05_23