



DESCRIPTION

| | |
|--------------------|--------------|
| Type | Swivel |
| Article-number | 141296L12444 |
| Colour | white |
| Energy Consumption | 26.7 W |
| Efficiency | 111 lm/W |
| Luminous Flux | 2963 lm |
| Current (sec) | 700 mA |
| Protection Class | IP |
| Energy-Label | E |
| Cooling | Passive |

LED

| | |
|------------------------|------------------|
| Color Temperature | 3000K |
| Color Rendering | CRI 92 |
| LES | 15 |
| Color Tolerance | 3-Step McAdam |
| Planckian Curve | BBBL |
| Spectrum | Premium White G7 |
| Photobiological safety | RG2 |

ELECTRICAL


| | |
|-------------------------------------|--------------------------|
| Power Supply | 220-240, 50-60Hz |
| Safety Class | 2 |
| Startup Time | < 1s |
| Overload- / Shortcircuit Protection | |
| Wiring / Adapter | connector 3/5 Pol (DALI) |
| Max Luminaires MCB | B16A 50 pcs |

Control

| | |
|---------------|---------|
| Control | DALI |
| Dimming Range | 1-100 % |

REFLECTOR

| | |
|------------|------------------|
| Technology | ULTRA |
| Material | Miro 20 / Miro 8 |
| FWHM | 24 / 55° |
| FWTM | 65 / 81° |



I-max : 5110 cd *

UGR : 25.6 / 21.6 (4H/8H - 70/50/20)

| H/m | D1/m | D2/m | Emax/lx/klm * |
|-----|------|------|---------------|
| 1.0 | 0.4 | 1.1 | 1724 |
| 2.0 | 0.9 | 2.1 | 431 |
| 3.0 | 1.3 | 3.2 | 192 |
| 4.0 | 1.7 | 4.2 | 108 |

Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023_05_23