



## DESCRIPTION

Type	Downlight
Article-number	141330L10527
Colour	silver
Energy Consumption	22.8 W
Efficiency	133 lm/W
Luminous Flux	3046 lm
Current (sec)	600 mA
Protection Class	IP
Energy-Label	D
Cooling	Passive

## LED

Color Temperature	4000K
Color Rendering	CRI 82
LES	15
Color Tolerance	3-Step McAdam
Planckian Curve	BBL
Spectrum	Neutral White G7
Photobiological safety	RG2

## ELECTRICAL


Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	connector 3/5 Pol (DALI)
Max Luminaires MCB	B16A - 50 pcs

## Control

Control	On/Off
---------	--------

## REFLECTOR

Technology	ULTRA
Material	Miro 4 Silver
FWHM	24°
FWTM	55°



I-max : 11223 cd \*

UGR : 21.3 (4H/8H - 70/50/20)

H/m	D/m	E <sub>max</sub> /lx/klm *
1.0	0.4	3685
2.0	0.8	921
3.0	1.3	409
4.0	1.7	230

**Other configurations, accessories or controls like DALI or Wireless on request**

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023\_05\_22