


DESCRIPTION

Type	Downlight
Article-number	141330L11202
Colour	black
Energy Consumption	15.1 W
Efficiency	138 lm/W
Luminous Flux	2085 lm
Current (sec)	400 mA
Protection Class	IP
Energy-Label	C
Cooling	Passive

LED

Color Temperature	3500K
Color Rendering	CRI 90
LES	15
Color Tolerance	2-Step McAdam
Planckian Curve	BBBL
Spectrum	Premium White G7 HE+
Photobiological safety	RG1

ELECTRICAL


Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	connector 3/5 Pol (DALI)
Max Luminaires MCB	B16A - 50 pcs

Control

Control	CASAMBI
Dimming Range	100 %

REFLECTOR

Technology	ULTRA
Material	Miro 20 Silver
FWHM	64°
FWTM	84°



I-max : 2093 cd *

UGR : 22.7 (4H/8H - 70/50/20)

H/m	D/m	E _{max} /lx/klm *
1.0	1.2	963
2.0	2.5	241
3.0	3.7	107
4.0	5.0	60

Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023_05_22