

GENERAL

Article-number	141369
Type	Track Spotlight
colours	silver, black, white
Power consumption	< 16 W
Efficiency	80 lm/W .. 135 lm/W
Luminous Flux	863 lm .. 2072 lm
Energy-Label	F .. D
Protection Class	IP20
Cooling	Passive

LED

CRI	CRI > 82 -> 92
Color Temperature	2700K, 3000K, 3500K, 4000K
Color Tolerance	3-Step McAdam



ELECTRICAL

Wiring / Adapter	3-Phase Adapter
Tracks	Globaltrack, Stucchi, Eutrac
Safety Class	2
Startup Time	< 1 s
Overload Protection	
Short Circuit Protection	
Power Supply	220-240 50-60Hz
Environment	0° - 30°C typical Ta 25°C


Control

Control	CASAMBI, ON/OFF, DALI
Dimming Range	1-100 %


REFLECTORS : ULTRA Technology




Spot



Medium



Flood



Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023_10_31