



DESCRIPTION

Type	Downlight
Article-number	141382L10047
Colour	black
Energy Consumption	30.1 W
Efficiency	143 lm/W
Luminous Flux	4292 lm
Current (sec)	800 mA
Protection Class	IP
Energy-Label	C
Cooling	Passive

LED

Color Temperature	3000K
Color Rendering	CRI 82
LES	18,5
Color Tolerance	3-Step McAdam
Planckian Curve	BBBL
Spectrum	Premium White G7
Photobiological safety	RG2

ELECTRICAL

Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	connector 3/5 Pol (DALI)
Max Luminaires MCB	B16A - 50 pcs

Control

Control	On/Off
---------	--------

REFLECTOR

Technology	ULTRA
Material	Miro 8 Silver
FWHM	15°
FWTM	30°



I-max : 7154 cd/klm *

UGR : 18.6 (4H/8H - 70/50/20)

H/m	D/m	Emax/lx/klm *
1.0	0.3	7154
2.0	0.5	1789
3.0	0.8	795
4.0	1.1	447

Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023_08_09