



## DESCRIPTION

|                    |              |
|--------------------|--------------|
| Type               | Downlight    |
| Article-number     | 141382L10520 |
| Colour             | silver       |
| Energy Consumption | 34.2 W       |
| Efficiency         | 129 lm/W     |
| Luminous Flux      | 4419 lm      |
| Current (sec)      | 900 mA       |
| Protection Class   | IP           |
| Energy-Label       | D            |
| Cooling            | Passive      |

## LED

|                        |                   |
|------------------------|-------------------|
| Color Temperature      | 2700K             |
| Color Rendering        | CRI 90            |
| LES                    | 19                |
| Color Tolerance        | 2-Step McAdam     |
| Planckian Curve        | BBL               |
| Spectrum               | Warm White G7 HE+ |
| Photobiological safety | RG1               |

## ELECTRICAL


|                                     |                          |
|-------------------------------------|--------------------------|
| Power Supply                        | 220-240, 50-60Hz         |
| Safety Class                        | 2                        |
| Startup Time                        | < 1s                     |
| Overload- / Shortcircuit Protection |                          |
| Wiring / Adapter                    | connector 3/5 Pol (DALI) |
| Max Luminaires MCB                  | B16A - 50 pcs            |

## Control

|         |        |
|---------|--------|
| Control | On/Off |
|---------|--------|

## REFLECTOR

|            |               |
|------------|---------------|
| Technology | ULTRA         |
| Material   | Miro 4 Silver |
| FWHM       | 24°           |
| FWTM       | 51°           |



I-max : 3654 cd/klm \*

UGR : 18.8 (4H/8H - 70/50/20)

| H/m | D/m | E <sub>max</sub> /lx/klm * |
|-----|-----|----------------------------|
| 1.0 | 0.4 | 3654                       |
| 2.0 | 0.8 | 914                        |
| 3.0 | 1.3 | 406                        |
| 4.0 | 1.7 | 228                        |

**Other configurations, accessories or controls like DALI or Wireless on request**

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023\_08\_09