

DESCRIPTION

Type	Downlight
Article-number	141382L11569
Colour	silver
Energy Consumption	30.1 W
Efficiency	150 lm/W
Luminous Flux	4531 lm
Current (sec)	800 mA
Protection Class	IP C
Energy-Label	C
Cooling	Passive

LED

Color Temperature	4000K
Color Rendering	CRI 80
LES	18,5
Color Tolerance	3-Step McAdam
Planckian Curve	BBL
Spectrum	Neutral White G7
Photobiological safety	RG1

ELECTRICAL


Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	connector 3/5 Pol (DALI)
Max Luminaires MCB	B16A - 50 pcs

Control

Control	CASAMBI
Dimming Range	100 %

REFLECTOR

Technology	ULTRA
Material	Miro 20 Silver
FWHM	65°
FWTM	81°



I-max : 966 cd/klm *

UGR : 22.2 (4H/8H - 70/50/20)

H/m	D/m	E _{max} /lx/klm *
1.0	1.3	937
2.0	2.6	234
3.0	3.9	104
4.0	5.1	59

Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023_05_23