

DESCRIPTION

Type	Downlight
Article-number	141382L11751
Colour	black
Energy Consumption	26.0 W
Efficiency	129 lm/W
Luminous Flux	3364 lm
Current (sec)	700 mA
Protection Class	IP
Energy-Label	D
Cooling	Passive

LED

Color Temperature	3500K
Color Rendering	CRI 90
LES	20
Color Tolerance	3-Step McAdam
Planckian Curve	BBBL
Spectrum	Premium White G7
Photobiological safety	RG1

ELECTRICAL


Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	connector 3/5 Pol (DALI)
Max Luminaire MCB	B16A - 50 pcs

Control

Control	CASAMBI
Dimming Range	100 %

REFLECTOR

Technology	ULTRA
Material	Miro 20 Silver
FWHM	65°
FWTM	81°



I-max : 966 cd/klm *

UGR : 21.1 (4H/8H - 70/50/20)

H/m	D/m	E _{max} /lx/klm *
1.0	1.3	937
2.0	2.6	234
3.0	3.9	104
4.0	5.1	59

Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023_05_23