




DESCRIPTION

Type	Swivel
Article-number	141428L10120
Colour	silver
Energy Consumption	11.8 W
Efficiency	88 lm/W
Luminous Flux	1035 lm
Current (sec)	350 mA
Protection Class	IP
Energy-Label	F
Cooling	Passive

LED

Color Temperature	3000K
Color Rendering	CRI 92
LES	6
Color Tolerance	3-Step McAdam
Planckian Curve	BBBL
Spectrum	Warm White G7
Photobiological safety	RG1

ELECTRICAL


Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	connector 3/5 Pol (DALI)
Max Luminaires MCB	B16A - 50 pcs

Control

Control	On/Off
---------	--------

REFLECTOR

Technology	ULTRA
Material	Miro 8 Silver
FWHM	13°
FWTM	27°



I-max : 9205 cd *

UGR : 20.1 (4H/8H - 70/50/20)

H/m	D/m	Emax/lx/klm *
1.0	0.2	8183
2.0	0.5	2046
3.0	0.7	909
4.0	0.9	511

Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023_05_22