

## DESCRIPTION

Type	Downlight
Article-number	141530L10418
Colour	silver
Energy Consumption	11.5 W
Efficiency	139 lm/W
Luminous Flux	1597 lm
Current (sec)	300 mA
Protection Class	IP
Energy-Label	C
Cooling	Passive

## LED

Color Temperature	3500K
Color Rendering	CRI 90
LES	9
Color Tolerance	2-Step McAdam
Planckian Curve	BBBL
Spectrum	Premium White HE G7 HE+
Photobiological safety	RG1

## ELECTRICAL


Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	connector 3/5 Pol (DALI)
Max Luminaires MCB	B16A - 50 pcs

## Control

Control	CASAMBI
Dimming Range	100 %

## REFLECTOR

Technology	ULTRA
Material	Miro 4 Silver
FWHM	23°
FWTM	55°



I-max : 5973 cd \*

UGR : 22.0 (4H/8H - 70/50/20)

H/m	D/m	E <sub>max</sub> /lx/klm *
1.0	0.4	3740
2.0	0.8	935
3.0	1.2	416
4.0	1.6	234

### Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023\_05\_22