



## DESCRIPTION

|                    |                 |
|--------------------|-----------------|
| Type               | Track Spotlight |
| Article-number     | 141564L10457    |
| Colour             | black           |
| Energy Consumption | 42.0 W          |
| Efficiency         | 98 lm/W         |
| Luminous Flux      | 4135 lm         |
| Current (sec)      | 1050 mA         |
| Protection Class   | IP 20           |
| Energy-Label       | E               |
| Cooling            | Passive         |

## LED

|                        |               |
|------------------------|---------------|
| Color Temperature      | 2700K         |
| Color Rendering        | CRI 92        |
| LES                    | 15            |
| Color Tolerance        | 3-Step McAdam |
| Planckian Curve        | BBL           |
| Spectrum               | Warm White G7 |
| Photobiological safety | RG2           |

## ELECTRICAL


|                                     |                       |
|-------------------------------------|-----------------------|
| Power Supply                        | 220-240, 50-60Hz      |
| Safety Class                        | 2                     |
| Startup Time                        | < 1s                  |
| Overload- / Shortcircuit Protection |                       |
| Wiring / Adapter                    | 3-Phase Adapter       |
| Max Luminaires MCB                  | B16A 27 pcs           |
| Tracks                              | Global Stucchi Eutrac |

## Control

|         |        |
|---------|--------|
| Control | On/Off |
|---------|--------|

## REFLECTOR

|            |               |
|------------|---------------|
| Technology | ULTRA         |
| Material   | Miro 4 Silver |
| FWHM       | 24°           |
| FWTM       | 51°           |



I-max : 16261 cd \*

UGR : 19.3 (4H/8H - 70/50/20)

| H/m | D/m | E <sub>max</sub> /lx/klm * |
|-----|-----|----------------------------|
| 1.0 | 0.4 | 3932                       |
| 2.0 | 0.9 | 983                        |
| 3.0 | 1.3 | 437                        |
| 4.0 | 1.7 | 246                        |

## Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023\_05\_24