



### DESCRIPTION

Type	Track Spotlight
Article-number	141564L10951
Colour	silver
Energy Consumption	31.1 W
Efficiency	137 lm/W
Luminous Flux	4275 lm
Current (sec)	800 mA
Protection Class	IP 20
Energy-Label	C
Cooling	Passive

### LED

Color Temperature	3500K
Color Rendering	CRI 90
LES	15
Color Tolerance	2-Step McAdam
Planckian Curve	BBBL
Spectrum	Premium White G7 HE+
Photobiological safety	RG1

### ELECTRICAL


Power Supply	220-240, 50-60Hz
Safety Class	2
Startup Time	< 1s
Overload- / Shortcircuit Protection	
Wiring / Adapter	3-Phase Adapter
Max Luminaires MCB	B16A 27 pcs
Tracks	Global Stucchi

### Control

Control	DALI
Dimming Range	1-100 %

### REFLECTOR

Technology	ULTRA
Material	Miro 20 Silver
FWHM	66°
FWTM	80°



I-max : 4079 cd \*

UGR : 23.6 (4H/8H - 70/50/20)

H/m	D/m	E <sub>max</sub> /lx/klm *
1.0	1.3	778
2.0	2.6	194
3.0	3.9	86
4.0	5.2	49

### Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2023\_05\_24