



GENERAL

| | |
|-------------------|----------------------|
| Article-number | 141820 |
| Type | Downlight |
| colours | silver, black, white |
| Power consumption | < 26 W |
| Efficiency | 99 lm/W .. 143 lm/W |
| Luminous Flux | 1158 lm .. 3588 lm |
| Energy-Label | E .. C |
| Protection Class | IP20 |
| Cooling | Passive |

LED

| | |
|-------------------|----------------------------|
| CRI | CRI > 82 -> 92 |
| Color Temperature | 2700K, 3000K, 3500K, 4000K |
| Color Tolerance | 2-Step McAdam |

ELECTRICAL

| | |
|--------------------------|---------------------------|
| Wiring / Adapter | connector 3/5 PoI (DALI) |
| Safety Class | 2 |
| Startup Time | < 1 s |
| Overload Protection | |
| Short Circuit Protection | |
| Power Supply | 220-240 50-60Hz |
| Environment | 0° - 30°C typical Ta 25°C |


Control

| | |
|---------------|-----------------------|
| Control | ON/OFF, CASAMBI, DALI |
| Dimming Range | 100 % |


REFLECTORS : SPUN Technology



Spot



Wide Flood



Other configurations, accessories or controls like DALI or Wireless on request

The technical data represent rated values for an ambient temperature of 25°C. The data values for the luminous flux are initially subject to a tolerance of +/- 10%, those for the the electrical connected load are initially subject to a tolerance of +/- 10%, those for the CRI +/- 1.5 and those for the colour temperature are initially subject to a tolerance of +/- 150 K. Errors and omission excepted. Subject to change without prior notice. Last update 2024_09_17